

product data



flood detector 869M Hz

What is a Flood Detector?

The flood detector is a neat, unobtrusive radio sensor that provides an early warning of potential flood situations. The unit can be placed on the floor under a sink or in a bathroom, next to the toilet or near the bath.

Who is it for?

The flood detector provides added reassurance to any homeowner or resident, giving extra protection to individuals who are likely to be at risk from leaving taps turned on.

How does it work?

The flood detector has three sensors. When two of the sensors make contact with water it provides two types of alarm - the first is a local audible alarm and the second sends a signal to a Lifeline home unit or other Tunstall telecare enabled systems. The Lifeline home unit automatically raises a call to the monitoring centre where the operator can identify what type of detector has initiated the call, allowing the most appropriate and immediate action to be taken.

Why is it needed?

A blocked sink, toilet, or taps being left on unattended could quickly lead to a flood causing damage to carpets, decorations and electrical equipment with potentially dangerous consequences. The after effects of a flood could not only result in extensive repair costs and increased insurance premium but also long term damage to health, particularly in winter.



All the reassurance you need

Tunstall

Features and benefits

- **Transmission to class 1 radio receiver** - ensuring that signals from sensors are reliably received, when linked to Lifeline home unit and other Tunstall telecare enabled systems
- **Dedicated frequency** - operates on the dedicated European 869 MHz social alarm frequency for reliable, future proofed operation
- **Range** - radio range is up to 50m, ideal for larger properties
- **Automatic low battery warnings** - ensuring optimum operation at all times (on radio battery)
- **5 year battery life on radio circuit** - up to 10,000 trigger operations are possible (under normal operating conditions)

Technical details

Weight:	142g
Dimensions:	90 x 31mm (W x D)
Radio frequency:	869.2125 MHz VHF integral transmitter
Radio range:	Up to 50m
Power supply:	Detector battery: 1 x 9V Alkaline, replaceable Radio battery: 3V lithium cells, non replaceable
Battery life:	Radio: 5 years Detector: 1 year
Battery disposal:	In accordance with current legislation

Standards:

EMC:	ETS 300 683:1997, EN 50130-4:1995
Safety:	EN60950:2000
Radio trigger:	EN 300 220-3V1.1.1 (09-2000)
CE:	Compliant
Design, Manufacture, Installation and Service:	1509001: 2000

Part Number: 67005/37

Please Note: A Class 1 receiver is necessary for "highly reliable SRD (short range device) communications media, eg serving human life inherent systems".

Tunstall

www.emergencyresponse.ie

Tunstall is a sunder member of the Continua Health Alliance

Our policy of continual development means that product specification and appearance may change without notice. Tunstall does not accept responsibility for any errors and omissions contained within this document.

© 2007 Tunstall Group Ltd. @TUNSTALL, AMIE and LIFELINE are registered trademarks.

Emergency Response Ltd Ryland Road Bunclody Enniscorthy Co Wexford Tele I:
1850 247 999 [Email: sales@emergencyresponse.ie](mailto:sales@emergencyresponse.ie)



F012477